

標準品 T-25 縦断走行用 内幅300~600

製品長	L=2000, L=1500	
模	縞鋼板模様	○
様	格子模様	○
様	無地	×

ボルト連結孔

ボルト連結孔

ボルト連結孔

呼び名 (幅a×高c)	各部の寸法 (mm)						参考質量 (kg)	
	B	H	c1	d	e	R	L=2000	L=1500
300	500	445	95	45	65	360	365	300
		545					420	345
		645					475	385
		745					575	460
		845					645	515
		945					715	565
		1045					885	695
		1145					965	755
		1245					1045	815
400	610	560	110	50	70	470	505	420
		660					565	465
		760					615	500
		860					740	600
		960					815	655
		1060					885	710
		1160					1075	850
		1260					1160	910
		1360					1245	980
500	720	575	125	55	80	600	565	515
		675					620	565
		775					725	615
		875					790	670
		975					860	730
		1075					1035	915
		1175					1115	980
		1275					1200	1050
		1375					1425	1125
1475	1520	1200						
1575	1615	1270						
600	830	590	140	60	70	730	670	610
		690					730	665
		790					790	720
		890					910	775
		990					980	835
		1090					1055	895
		1190					1245	1095
		1290					1330	1170
		1390					1420	1245
		1490					1665	1325
		1590					1765	1400
		1690					1870	1485